


Kontrollrohre
Inspection-pipes
Conduits à regard




Abmessungen für 1,5 mm Rohrteile
Dimensions for 1,5 mm piping
Dimensions pour tuyauterie en épaisseur 1,5 mm

DN	Ø d	A	B	C	E	F	L	kg
60	-	-	-	-	-	-	-	-
80	77	80	-	-	-	-	200	1,05
100	100	115	-	-	-	-	200	1,25
120	120	115	-	-	-	-	200	1,45
140	136	115	-	-	-	-	200	1,55
150	150	115	-	-	-	-	200	1,65
175	175	115	-	-	-	-	200	1,85
200	200	115	-	-	-	-	200	2,00
224	220	115	-	-	-	-	200	2,25
250	250	115	-	-	-	-	200	2,40
300	300	115	-	-	-	-	200	2,85
350	350	115	-	-	-	-	200	3,40
400	399	115	-	-	-	-	200	3,80

Dichtung Neoprene (CR), -30 max. 90 °C.
Material of seal Neoprene (CR), -30 max. 90 °C.
Joint en Néoprène (CR), -30 max. 90 °C.

Verstärkte, druckstoßfeste Ausführung auf Anfrage.
Reinforced, shock-explosion proof version on request.
Version résistante à la surpression sur demande.


Reinigungsrohre
Cleaning-pipes
Tuyaux de nettoyage



200	200	224	350	-	-	-	486	4,70
224	220	224	350	-	-	-	486	5,20
250	250	224	350	-	-	-	486	5,70
300	300	350	350	-	-	-	486	6,30
350	350	350	350	-	-	-	486	8,40
400	399	350	350	-	-	-	486	9,10
450	448	500	350	-	-	-	486	11,60
500	498	500	350	-	-	-	486	12,80
560	558	500	350	-	-	-	486	14,30
630	628	500	350	-	-	-	486	16,00

Dichtung EPDM hell, -35 max. 80 °C.
Material of seal EPDM bright, -35 max. 80 °C.
Joint en EPDM clair, -35 max. 80 °C.


Kontrollstutzen ohne Gummiendeckel
Inspection T-pieces without rubber cover
Manchons de contrôle sans couvercle de caoutchouc



60+80	-	-	-	-	-	-	-	-
100	100	100	79	-	-	-	165	0,70
120	120	100	89	-	-	-	165	0,80
150	150	120	100	-	-	-	198	1,20
175	175	150	114	-	-	-	225	1,50
200	200	150	125	-	-	-	225	1,75
250	250	150	150	-	-	-	225	2,20
300	300	150	177	-	-	-	225	2,55

Abgang Ø A für Gummiendeckel beachten.

Gummiendeckel
Rubber covers
Couvercle de caoutchouc



Abmessungen
Dimensions
Dimensions

DN	Ø d	A	B	C	E	F	L	kg
60	-	-	-	-	-	-	-	-
80	-	79	109	6	22	-	-	0,10
100	-	101	122	5	22	-	-	0,15
120	-	121	140	6	24	-	-	0,20
150	-	151	176	7	33	-	-	0,35
175	-	176	205	7	35	-	-	0,45
200	-	201	228	8	40	-	-	0,60
250	-	251	280	10	42	-	-	0,90
300	-	301	328	8	40	-	-	1,35

Zusätzliche Deckel-Arretierungen
Additional cover locks
Verrouillage supplémentaire du couvercle



100	-	-	-	100	-	-	-	0,30
120	-	-	-	120	-	-	-	0,35
150	-	-	-	150	-	-	-	0,55

DN	Nr.	1,5 mm grundriert 1,5 mm primed 1,5 mm peint	2 mm grundriert 2 mm primed 2 mm peint	3 mm grundriert 3 mm primed 3 mm peint	1,5 mm verzinkt 1,5 mm galvanizé 1,5 mm galvanisé	1 mm Chromnickelstahl 1 mm stainless steel 1 mm acier inoxydable	1,5 mm Chromnickelstahl 1,5 mm stainless steel 1,5 mm acier inoxydable	2 mm Chromnickelstahl 2 mm stainless steel 2 mm acier inoxydable
60	-	-	-	-	-	-	-	-
80	11081190	-	-	-	11082190	11083190	-	-
100	11101190	-	-	-	11102190	11103190	-	12103190
120	11121190	-	-	13121190	11122190	11123190	-	12123190
140	11141190	-	-	-	11142190	11143190	-	-
150	11151190	-	-	13151190	11152190	11153190	-	12153190
175	11171190	-	-	13171190	11172190	11173190	-	12173190
200	11201190	-	-	13201190	11202190	11203190	-	12203190
224	11221190	-	-	-	11222190	11223190	-	-
250	11251190	-	-	13251190	11252190	11253190	-	12253190
300	11301190	-	-	13301190	11302190	11303190	-	12303190
350	11351190	-	-	13351190	11352190	11353190	-	12353190
400	11401190	-	-	13401190	11402190	11403190	-	12403190

2010

200	11201195	-	-	-	11202195	-	11203195	-	-
224	11221195	-	-	-	11222195	-	11223195	-	-
250	11251195	-	-	-	11252195	-	11253195	-	-
300	11301195	-	-	-	11302195	-	11303195	-	-
350	11351195	-	-	-	11352195	-	11353195	-	-
400	11401195	-	-	-	11402195	-	11403195	-	-
450	-	-	12451195	-	-	-	-	-	12453195
500	-	-	12501195	-	-	-	-	-	12503195
560	-	-	12561195	-	-	-	-	-	12563195
630	-	-	12631195	-	-	-	-	-	12633195

*) 2 mm

2020

60+80	Kontrollstutzen siehe T-Stücke S. 44.	Inspection T-pieces see T-pieces on page 44.	Manchons de contrôle voir pièces en T page 44.			
100	11101200	-	11102200	11103200	-	12103200
120	11121200	-	13121200	11122200	11123200	12123200
150	11151200	-	13151200	11152200	11153200	12153200
175	11171200	12171200	13171200	11172200	11173200	12173200
200	11201200	12201200	13201200	11202200	11203200	12203200
250	11251200	12251200	13251200	11252200	11253200	12253200
300	11301200	12301200	13301200	11302200	11303200	12303200

Observe outlet Ø A for rubber cover.

Respecter la sortie Ø A pour le couvercle de caoutchouc.

1040

DN	Natural rubber NR		Perbunan NBR		Neoprene CR	
	Nr.		Nr.		Nr.	
60	-	-	-	-	-	-
80	10085201	-	-	-	-	-
100	10105201	10106201	10108201			
120	10125201	10126201	10128201			
150	10155201	10156201	10158201			
175	10175201	10176201	10178201			
200	10205201	10206201	10208201			
250	10255201	10256201	10258201			
300	10305201	10306201	10308201			

3030

DN	Nr.	2 mm galvanisch verzinkt	2 mm electro galvanized	2 mm electro galvanisé
100	11102210	Für Kontrollstutzen Ø 100 und 120	For inspection T-piece Ø 100 and 120	Pour manchons de contrôle Ø 100 et 120
120	11122210	Für Kontrollstutzen Ø 150	For inspection T-piece Ø 150	Pour manchons de contrôle Ø 150
150	11152210	Für Kontrollstutzen Ø 175 bis 300	For inspection T-piece Ø 175 to 300	Pour manchons de contrôle Ø 175 à 300

3040