

FEATURES

- Compact valve intended for single acting actuator control
- Two maximum pressure ratings depending on coil power
- AC/DC interchangeability of the solenoid head without any need for disassembly of the valve
- The solenoid valves satisfy all relevant EC directives

GENERAL

Differential pressure See «SPECIFICATIONS» [1 bar = 100 kPa]
Maximum viscosity 40 cSt (mm²/s)
Response time 8 - 20 ms

fluids (*)	temperature range (TS)	seal materials (*)
air, inert gas, water, oil	- 25°C to + 80°C	NBR (nitrile)

MATERIALS IN CONTACT WITH FLUID

(*) Ensure that the compatibility of the fluids in contact with the materials is verified

	Brass body	Stainless steel body
Body	Brass	AISI 316L (1.4404)
Internal parts	Stainless steel	Stainless steel
Springs	Stainless steel	Stainless steel
Seat	Brass and stainless steel	Stainless steel
Seals	NBR	NBR
Shading coil	Copper	Copper

ELECTRICAL CHARACTERISTICS

Coil insulation class F
Connector Spade plug (cable Ø 6-10 mm)
Connector specification ISO 4400 / EN 175301-803, form A
Electrical safety IEC 335
Electrical enclosure protection Moulded IP65 (EN 60529)
Standard voltages DC (=): 24V - 48V
 (Other voltages and 60 Hz on request) AC (~): 24V - 48V - 115V - 230V / 50 Hz

prefix option	power ratings				operator ambient temperature range (TS) (C°)	replacement coil		type ⁽¹⁾
	inrush ~		holding ~			~	=	
	(VA)	(W)	(VA)	(W)		230 V/50 Hz	24 V DC	
SC	23	14	8	8 / 10,8	-25 to + 60	43005096	43005099	01
	55	23	10,5	9 / 11,2	-25 to + 60	400425-117	400425-142	02

⁽¹⁾ Refer to the dimensional drawings on the following page.


SPECIFICATIONS

pipe size	orifice size	flow coefficient Kv		operating pressure differential (bar)				power coil (W)		catalogue number				options			
				max. (PS)						brass		stainless steel		maintained man. operator	FPM	EPDM	
				min.	air (*)		water/oil (*)										
(G*)	(mm)	(m ³ /h)	(l/min)	~	=	~	=	~	=	~	=	~	=				
NC - Normally closed																	
1/4	2 ⁽³⁾	0,11	1,8	0	16	8	16	8	8	10,8	SCE374A001	SCE374A061	SCE374A031	SCE374A070	MS	V	E
					16	16	16	16	10,5	11,2	SCE374A016	SCE374A016	SCE374A046	SCE374A046	MS	V	E
	2,7	0,22	3,6	0	10	5	10	5	8	10,8	SCE374A002	SCE374A062	SCE374A032	SCE374A071	MS	V	E
					10	10	10	10	10,5	11,2	SCE374A017	SCE374A017	SCE374A047	SCE374A047	MS	V	E
	3,8	0,32	5,3	0	5	2	5	2	8	10,8	SCE374A003	SCE374A063	SCE374A033	SCE374A072	MS	V	E
					5	5	5	5	10,5	11,2	SCE374A018	SCE374A018	SCE374A048	SCE374A048	MS	V	E
U - Universal																	
1/4	2,7	0,22	3,6	0	8	-	4	-	8	10,8	SCE374A012	-	SCE374A042	-	MS	V	E
					8	4	4	4	10,5	11,2	SCE374A027	SCE374A027	SCE374A057	SCE374A057	MS	V	E
	3,8	0,32	5,3	0	4	-	4	-	8	10,8	SCE374A013	-	SCE374A043	-	MS	V	E
					4	2	4	2	10,5	11,2	SCE374A028	SCE374A028	SCE374A058	SCE374A058	MS	V	E
NO - Normally open																	
1/4 ⁽²⁾	2,5	0,22	3,6	0	10	-	10	-	8	-	SCE374A007	-	SCE374A037	-	MS	V	E
					10	10	10	10	10,5	11,2	SCE374A022	SCE374A022	SCE374A052	SCE374A052	MS	V	E

⁽²⁾ Pipe size of port 3: G 1/8.

⁽³⁾ Orifice size port 3: 2,5 mm

⁽⁴⁾ 1 → 3: 0,15 m³/h, 2,5 l/min



E

OPTIONS

- Valves can also be supplied with FPM (fluoroelastomer) and EPDM (ethylene-propylene) seals and discs. Use the appropriate optional suffix letter for identification
- Waterproof enclosure with embedded screw terminal coil according to protection class IP67, CEE-10 (prefix WP or WS)
- Explosionproof enclosures for use in zones 1/21-2/22, categories 2-3 to ATEX Directive 94/9/EC (see "Explosionproof solenoids" section)
- Class H coil (10,5 W/11,2 W), prefix HT, example: SCHTE374A016
- Oxygen service with seals and disc in FPM, suffix N, example: SCE374A016NV
- Other pipe connections are available on request
- Plug with visual indication and peak voltage suppression or with cable length of 2 m (see Solenoids, Coils & Accessories section)

INSTALLATION

- The solenoid valves can be mounted in any position without affecting operation
- Brass solenoid valves have 2 mounting holes in body
- Pipe connections 1/4 (G*) have standard combination thread according to ISO 228/1 and ISO 7/1. Pipe connections G 1/8 have standard thread according to ISO 228/1
- Installation/maintenance instructions are included with each valve

SPARE PARTS KIT

catalogue number	spare parts kit no.		
	~	=	maintained man. operator
SCE374A001/002/003	C140038	-	C140048
SCE374A031/032/033	C140038	-	C140072
SCE374A016/017/018	C140038	C140037	C140048
SCE374A046/047/048	C140038	C140037	C140072
SCE374A061/062/063	-	C140037	C140048
SCE374A070/071/072	-	C140037	C140072
SCE374A012/013	C140042	-	C140048
SCE374A042/043	C140042	-	C140072
SCE374A027/028	C140042	C140042	C140048
SCE374A057/058	C140042	C140042	C140072
SCE272A007	C140039	-	C140048
SCE272A037	C140039	-	C140072
SCE272A022	C140039	C140039	C140048
SCE272A052	C140039	C140039	C140072

ORDERING EXAMPLES:

SC	E	374	A	016	MS	230V / 50 Hz
SC	E	374	A	046	V	115V / 50 Hz
SC	E	374	A	002	MS	24V / DC
SC	E	374	A	061		230V / 50 Hz

prefix — pipe thread — basic number — voltage — suffix

ORDERING EXAMPLES KITS:

C140037 ⁽¹⁾	
C140038	V
C140038	E

basic number — suffix

⁽¹⁾ Standard suffixes E and V are also applicable to kits.

- Not available

DIMENSIONS (mm), WEIGHT (kg)



TYPE 01-02





Prefix "SC" Solenoid
Epoxy moulded
IEC 335 / ISO 4400
IP65

Type 01: SCE374A001/002/003/061/062/063/012/013/007

Type 02: SCE374A016/017/018/027/028/022

Type 01: SCE374031/032/033/070/071/072/042/043/037

Type 02: SCE374A046/047/048/057/058/052



type	prefix option	catalogue number	A	B	C	E	F	weight ⁽²⁾
01	SC	SCE374A001/002/003/061/062/063/012/013/007	70	35	20	75	30	0,340
		SCE374031/032/033/070/071/072/042/043/037	70	35	20	75	30	0,410
02	SC	SCE374A016/017/018/027/028/022	85	50	30	85	45	0,510
		SCE374A046/047/048/057/058/052	85	50	30	85	45	0,560

① Manual operator location.

② 2 mounting holes Ø M4, depth 6 mm.

⁽²⁾ including coil and connector.