

Pipeline Ancillaries

Strainers and Filters FI 1.01

Gasfilter for High Pressures




Technical Data

Connection DN	15 - 250
Connection G	3/8 - 2
Nominal Pressure PN	16 - 160
Temperature	80 °C
Medium	gases

Description

Gas filters protect plant and equipment such as regulators, valves, measuring equipment, safety valves and burners against damage or operational failure caused by contamination. They are essential for start-up as well as continuous operation. In systems equipped with multiple tube filters they may be used as a bypass filter instead of costly additional standby filters.

Cleaning is extremely simple and quick thanks to the quick-release locking of the filter element.



Installation can be carried out in any position; installation with the cover at the bottom is recommended.

Standard

- » filter medium made of skeletal polyester foam (for pore size and number of sheets see tables on right)
- » stainless steel support frame fitted with quick-release locking

Options

- » filter medium in various pore sizes (see table on right)
- » pressure gauges upstream and downstream of the filter element
- » various seal materials suitable for your medium
- » special versions on request

Operating instructions, know how and safety instructions must be observed. All the pressure has always been indicated as overpressure. We reserve the right to alter technical specifications without notice.



Filter Mat

mat no.	size of pores mm	dust restraint capacity with testdust, limit grain 0.005 mm	
80 (special)	0.150	clean	71%
		medium	85%
		dirty	91%
60	0.265	clean	63%
		medium	78%
		dirty	86%
45	0,370	clean	56%
		medium	72%
		dirty	82%
30	0.580	clean	55%
		medium	65%
		dirty	70%

Number if Filter Mats

nominal diameter			
G 3/8 - 2	DN 15 - 50	DN 65 - 125	DN 150 - 250
1 x Nr. 60	1 x Nr. 60	1 x Nr. 60 1 x Nr. 45	1 x Nr. 60 1 x NR. 45 1 x Nr. 30

Pipeline Ancillaries

Strainers and Filters FI 1.01

Gasfilter for High Pressures



Materials

Body	PN 16	up to DN 25 grey cast iron from DN 32 spheroidal cast iron
	PN 25 - 160	cast steel
Seal	Nova Universal	
Filter Mat	polyesterfoam with skeleton construction	
Supporting Frame	CrNiMo-steel	

Dimensions [mm] flange connection

size	PN	nominal diameter DN										
		15	20	25	32	40	50	65	80	100	125	150
A	16	-	150	160	180	200	230	290	310	350	400	400
	40	196	200	-	244	-	-	-	-	-	-	-
	63/160	210	230	-	-	-	-	-	-	-	-	-
B	16	-	110	125	130	135	150	170	160	190	250	275
	40	120	120	-	130	-	-	-	-	-	-	-
	63/160	120	145	-	-	-	-	-	-	-	-	-
C	16	-	160	185	215	220	255	285	275	345	410	490
	40	170	170	-	215	-	-	-	-	-	-	-
	63/160	170	200	-	-	-	-	-	-	-	-	-
øD	16	-	110	140	140	170	170	210	220	255	320	350
	40	110	110	-	140	-	-	-	-	-	-	-
	63/160	110	150	-	-	-	-	-	-	-	-	-
E	16 - 160						G 1/2		G 1			
F	16 - 160						G 1/4				G 1/2	

Weights [kg] flange connection


nominal pressure PN	nominal diameter DN										
	15	20	25	32	40	50	65	80	100	125	150
16	-	4.5	6	8.5	12.5	16.5	25	30	46	67	90
40	5.5	6.5	-	11	-	-	-	-	-	-	-
63/160	8	16	-	-	-	-	-	-	-	-	-

Dimensions [mm] BSP female connection

size	PN	nominal diameter G						
		3/8	1/2	3/4	1	1 1/4	1 1/2	2
A	16	90	90	120	140	140	170	170
	40	120	120	120	-	160	-	-
	63/160	120	120	120	-	-	-	-
B	16	65	65	110	125	130	135	150
	40	120	120	120	-	130	-	-
	63/160	120	120	120	-	-	-	-
C	16	120	120	165	185	215	220	255
	40	170	170	170	-	215	-	-
	63/160	170	170	170	-	-	-	-
øD	16	65	110	110	140	140	170	170
	40	110	110	110	-	140	-	-
	63/160	110	110	110	-	-	-	-
E	16 - 160	G 1/4	G 1/4	G 1/4	G 1/4	G 1/4	G 1/4	G 1/4

Weights (kg) BSP female connection

PN	nominal diameter G						
	3/8	1/2	3/4	1	1 1/4	1 1/2	2
16	1.5	1.5	3	4	5	7.5	10.5
40	5	5	5	-	7	-	-
63	6	6	6	-	-	-	-
160	8	8	8	-	-	-	-



Special designs on request.

The pressure has always been indicated as overpressure.

Mankenberg reserves the right to alter or improve the designs or specifications of the products described herein without notice.