

## SAUNA TEMPERATURE SENSOR TES NTC 10

TES NTC 10 temperature sensor is designed for automatic HVAC systems, especially for demanding conditions such as saunas, cold-rooms, freezers and stores.

Temperature is detected by an NTC thermistor with a nominal resistance of 10 k $\Omega$ /25 °C. Thermistor is outside the housing.

Housing is made of weather-proof siluminium, IP 67 also ensuring a good mechanical protection for the sensor.



### Technical data:

Sensor	10 k $\Omega$ NTC thermistor
Protection degree	IP 67
Housing	silumin cast
Cable entry	PG 11
Range	-50...120 °C
Accuracy	$\pm$ 0.2 °C (at 25 °C)
Dimensions	100 x 65 x 35 mm

### Temperature/Resistance:

°C	NTC 10 k $\Omega$	°C	NTC 10 k $\Omega$
120	389.0	25	10000.0
100	680.0	20	12490.0
90	917.7	15	15710.0
80	1258.0	10	19900.0
75	1480.0	5	25400.0
70	1752.0	0	32650.0
65	2082.0	-5	42340.0
60	2488.0	-10	55330.0
55	2968.0	-15	72980.0
50	3603.0	-20	97070.0
45	4368.0	-25	130400.0
40	5327.0	-30	177000.0
35	6532.0	-40	336500.0
30	8057.0	-50	670100.0

### Ordering guide:

Model	Product number	Description
TES NTC 10	1175100	sauna temperature sensor, 10 kohm / 25 °C

Products fulfil the requirements of directive 2004/108/EY and are in accordance with the standards EN61000-6-3: 2001 (Emission) and EN61000-6-2: 2001 (Immunity).

### Produal Oy

Keltakalliontie 18  
48770 Kotka  
FINLAND  
[www.produal.fi](http://www.produal.fi)

Puh: +358-5-230 9200  
Fax: +358-5-230 9210  
[info@produal.fi](mailto:info@produal.fi)